



## TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5

The extra-durable HM ULTRA 50 is made for continuous use: carbide-tipped, extremely wear-resistant and heat-resistant up to 800°C.

Available in Ø 12–65 mm with 50 mm cutting depth.

---

Product number: 6 31 27 013 01 1

## Details

- + Available in Ø 12–65 mm with 50 mm cutting depth.
- + Durability: 350 holes = 7 m total service life. Determined under optimal conditions: Ø18 mm, S235 20 mm.
- + Cost efficiency: Double the service life and higher cutting speed compared to HSS core drills – reduces costs for large quantities.
- + For tough everyday workshop use: Optimum performance for economical drilling – more holes, fewer tool changes.
- + Precise work: Innovative 3-flute design ensures smooth, chatter-free cutting and accurate drilling results.
- + Experience since 1977: Decades of core drilling expertise – your advantage in practice.

## Technical data

### TECHNICAL DATA

|                         |                     |
|-------------------------|---------------------|
| Material                | HM (carbide-tipped) |
| Vickers hardness (HV)   | 1 450 HV            |
| Heat resistance         | max. 800°C          |
| Bore Ø                  | 42 mm               |
| Drill core Ø approx.    | 34.5 mm             |
| Number of cutting edges | 6                   |
| Total length            | 80 mm               |
| Core drill holder       | M18 x 6 P1,5        |
| Cutting depth           | 50 mm               |

## Suitable for the following tools

- > KBM 65 U (110 V)
- > KBM 50 U (110 V)



## Application examples

