



FEIN



HSS Dura 50 core bit with QuickIN holder

Extremely shock and impact resistant for demanding use in steel and stainless steel. TiN coating ensures high wear resistance and long service life in steel construction.

Available in Ø 12–50 mm with 50 mm cutting depth.

Product number: 6 31 33 220 06 8

Details

- + Resistant: Drill body and cutting edges made from the same HSS steel. This results in increased impact and shock resistance – ideal for assembly, steel construction and rough surfaces.
- + Minimal friction: TiN coating heat-resistant up to 650°C - for maximum performance and service life.
- + Durability: 170 holes = 3.4 m total service life. Determined under optimal conditions (Ø 18 mm, S235, 20 mm).
- + Fast & efficient: Higher cutting speeds thanks to TiN - for noticeably more work progress.
- + Versatile: Ideal for steel up to 750 N/mm², stainless steel, aluminium - also suitable for short-term dry drilling.
- + Experience since 1977: Decades of core drilling expertise – your advantage in practice.
- + Accessories: 100 mm centring pin. Order number: 63134998310.

Technical data

TECHNICAL DATA

Material	HSS
Rockwell hardness (HRC)	64 HRC
Coating	Titan-Nitrid (TiN)
Coating thickness	3 µm
Coating strength	1 550 HV
Heat resistance	max. 650°C
Bore Ø	22 mm
Drill core Ø approx.	14 mm
Number of cutting edges	6
Max. cutting depth	55 mm
Total length	86 mm
Core drill holder	QuickIN



Inner bore Ø

6.35 mm

Cutting depth

50 mm

Suitable for the following tools

- > KBU 35 PQW
- > KBM 50 U (110 V)
- > AKBU 35 PMQW AS
- > KBM 65 U (110 V)

Application examples

